

Input	Lumens/Watt	Dimmable	CRI	Driver	Colour Temp.
230V	13,500lm	Available	>80	Integral	5000K

Warranty	Chip	Beam Angle	PFC	Material	IP
5yrs	126pcs 3030	>90deg	0.95	Aluminium	IP65

## **LED Highbay IP65**

Introducing a New Generation of Highbay lighting. Gone is the inefficient Mercury Vapour, Metal Halide and even HPS metal reflector highbays.

Latest generation introduces massive system efficiency with up to 135 Lumens per Watt. The HUGO LED highbay features a highly efficient driver matched to 3030 SMD LEDs. Supplied complete with flex & plug top for quick installation

## **KEY FEATURES**

- Current DC32-45V 3.4 Amps
- Complete with 1.5M flex & plug
- Working Temp -30°c to +50°c Humidity 10% to 95%
- Dimming options DALI 1-10V on request
- Suitable to operate with motion sensors
- Instant on off no cooling re strike time
- Constant Current Driver
- LED Life 50,000hrs (TM21 L70)
- Optical grade PC UV and Fire resistant lens
- Stainless Steel screws
- Excellent uniformity
- Compact Size
- Light Weight 3.0kg
- IES Files (Refer Website)
- Aluminium body
- Mounting hook
- SMH Ratio Nom 1.25:1



- CRI >80 (R9=4)
- Over Current Protection
- SAA Electrical approval

			,	DIMENSIONS
HB100-5	100W	13,500lm	126pcs	D:320mm, H: 150mm



