

Input	Colour Temp.K	Dimmable	CRI	IP	Life
230V	4000K	No	> 90	IP40	50,000hr L70

Frame	Diffuser	PF	Warranty	Efficacy	Beam Angle
WhiteAluminium	PS	0.95	5yrs	To 100Lm/W	112 deg

MOUNTING	
Surface	TBar/Plaster/Wire

Low Glare UGR<19 High CRI >90 Troffer LED panel

White frame finish to match T Bar rails Even light distribution

Ideal for commercial applications Low running temperature



KEY FEATURES

- Aluminium Frame Powder Coated White
- To Suit T Bar ceilings, can be surface/wall mounted with kit (available separately) or plaster frame (not supplied)
- Flicker free
- Edge lit SMD4014
- Long life 50,000hr L70
- Energy saving up to 50% compared to T8
- Frame thickness 10mm
- UGR >19
- Operating Temp -20° + 45°
- 1.2M Flex & Plug fitted SAA Approved 0.75mm
- SAA Approved driver, flicker free
- Phase cut off, 1-10V, DSI, DALI available on request
- Quick connectors with SAA approved 0.5mm cable
- Seismic restraint attachments available (4pcs per kit)
- Surface kits screw-less type on request
- Will suit all plaster frames
- 5 years warranty

Dimming options : Phase cut-off :PH
 1-10V :10V
 DALI :DA

SKU CODE	WATT	LUMEN (Nom)	DIMENSIONS	WEIGHT
PAN1200-UGR19-90	60Watt	6,000lm	1195x595	4.6kg
PAN600-UGR19-90	40Watt	4000lm	595x595	2.5kg
PAN300-UGR19-90	40Watt	4000lm	1195x295	2.65kg