

3 CCT Selectable LED Panel

White frame finish to match T Bar rails.
Even light distribution ideal for commercial applications. Low running temperature.



Key Features

- In line selectable colour temperature (K) switch
- Aluminium Frame Powder Coated White
- To suit T Bar ceilings, can be surface/wall mounted with kit (available separately) or plaster frame (not supplied)
- Flicker free
- Edge lit SMD3014 (240pcs & 476pcs) 36V DC 900/1100mA
- Long life 50,000hr L70
- Energy saving up to 50% compared to T8
- Frame thickness 10mm
- UGR >19
- Operating Temp -20° + 45°
- 1.2M Flex & Plug fitted SAA Approved 0.75mm
- SAA Approved driver
- Quick connectors with SAA approved 0.5mm cable
- Seismic restraint attachments available (4pcs per kit)
- Surface kits screw-less type on request
- Will suit all plaster frames
- Minimum order number required
- Other colour temperatures available on request
- Dimming options: Phase cut-off: PH
1-10V: 10V
DALI: DA

SKU Code	PAN300-URG19-90	PAN600-URG19-90	PAN1200-URG19-90
Input	230V	230V	230V
Wattage	40W	40W	60W
Lumens	3,600	3,600	6,000
LED Qty	224pcs	224pcs	476pcs
Dimensions	L: 1,195mm H: 295mm	L: 595mm H: 595mm	L: 1,195mm H: 595mm
Weight	2.45KG	2.45KG	4.45KG
Dimmable	No	No	No
CRI	90+	90+	90+
Driver	AC	AC	AC
Colour Temp	4,000K	4,000K	4,000K
Warranty	3 years	3 years	3 years
Chip	SMD 3014	SMD 3014	SMD 3014
Beam Angle	112°	112°	112°
PFC	0.95	0.95	0.95
Material	Aluminium	Aluminium	Aluminium
IP	IP40	IP40	IP40
Diffuser	PMMA+PS	PMMA+PS	PMMA+PS
Mounting	Surface/ T Bar/ Plaster/Wire	Surface/ T Bar/ Plaster/Wire	Surface/ T Bar/ Plaster/Wire
UGR	19	19	19
Stock	Indent	Indent	Indent