HUGO

3CCT Quick Fit Batten

A contemporary design LED batten for both commercial and residential applications. The opal diffuser supplies even illumination whilst minimising glare. Quick Fit with push twin terminals, detachable light source from base for easy mounting. Clean and modern design

Key Features

- Center feed cable entry
- Plug and play connector
- 3 way push terminals
- Long life of 50,000hr
- Integrated LED board
- Integrated driver
- 3yr warranty
- 3CCT
- CRI 80+
- Uniform light effect
- Surface mounted or Suspended mounting





PRODUCT DATA BAT1200-3 1500-3

| | SKU Code | BAT1200-3 | BAT1500-3 | |
|------------|-----------------|-------------------|-----------|--|
| | Input | 220-240V | | |
| 1 | Wattage | 40W | 60W | |
| | Lumen | 4,200m | 6,300lm | |
| | Dimensions | 65x1200mm | 65x1500mm | |
| | Projection | 65mm | | |
| | Weight | 1.8kg | 2.2kg | |
| 1 | Dimmable | No 80+ | | |
| | CRI | | | |
| | Driver | Constant Current | | |
| | Colour Temp | 3000K 4000K 6000K | | |
| | Warranty | 3 years | | |
| Beam Angle | | 120 | 12Odeg | |
| | Material ABS Er | | nd cap | |
| | IP | IP20 | | |
| | PF | | | |
| | Diffuser | | | |
| | Surge Prot. | Зkv | | |
| | Mounting | Surface/suspended | | |
| | Colour | White | | |
| | | | | |



hugolighting.com | P: 03 942 1272 | E: info@hugolighting.com