

Watt	Lumens	Dimmable	CRI	Cut-Out	Overall
12W	1,100lm	Yes	85-90	95-110mm	120mm

Classification	Input	Colour Temp.	Life	Recess	Material
IC-F	230V Driver	3,000 - 4,000K	40,000hr	60mm	Aluminium

IP	Beam Angle	Warranty	Colour		PFC
IP65	120 deg	5yrs	Matt White	Brush Chrome	0.90

## DLEK231 12W DIMMABLE LED DOWNLIGHT

High quality LED dimmable downlight suitable for residential and commercial applications and suitable for replacement of 50 Watt dichroic and 100 watt incandescent downlights.

A wide beam angle of 120 deg providing even illumination and minimizing shadows.

High lumen output and low running costs, minimal heat and long service life.

This downlight is IC-F compliant and Energy Star rated

85+ CRI LED Chips

Quality has not been compromised

### KEY FEATURES

- High Lumen output 1,100 Lumens
- 3,000K colour temperature Warm White
- Easy installation and wiring with quick snap terminal cover
- Long Life 40,000hr
- Dimmable with Leading and trailing edge dimmers
- Wide beam angle (120deg)
- Low running costs only 12W with PFC 0.90
- Complete with driver (hard wired)
- Driver and Luminaire IC Rated and may be covered by approved fixed ceiling Insulation



SKU CODE	TRIM	LED COLOUR
DLEK231W	MATT WHITE	3,000K - 4,000K
DLEK231BC	BRUSHED CH	3,000K

Note:  
RED only driver Complies with Annex ZA of AS/NZS 60598.2.2:2001 Luminaires  
Part 2.2: Particular requirements  Recessed  
luminaires incorporating New Zealand  only  
Amendment A.

