## HUGO

## PRODUCT DATA DLEK926

## 10W IP65 Tilt Fire Rated to British Standard LED Downlight

90min fire rated to british standard (BS 476-21:1987). Fully sealed with gasket fitted. IP65 and tilt due to 'AIR SEAL'. Citizen COB LED Downlight.

Fully dimmable with a standard dimming mech with no special control gear required.

Suitable for residential and commercial applications.





ABUTTED & COVERED
----------------------

- High lumen output 900lm
- CRI 97+
- Aluminium reflector
- 3,000K or 4,000K colour temperature
- Long life 40,000hr
- Dimmable with leading and trailing edge dimmers
- Easy installation and wiring (extra large terminals)
- 60° beam angle
- +  $30^{\circ}$  tilt angle
- Complete with driver



SKU Code	DLEK9263K	DLEK9264K
Input	230V	230V
Wattage	10W	10W
Lumen	900lm	900lm
Dimensions	100mm	100mm
Cutout	92mm	92mm
Recess	64mm	64mm
Dimmable	Yes	Yes
CRI	97+	97+
Material	Aluminium & Steel	Aluminium & Steel
Colour Temp	3000K	4000K
Rating	IC-F	IC-F
Warranty	5 years	5 years
Beam Angle	60°	60°
Tilt Angle	30°	30°
Fire Rated	90 min	90 min
Life	40,000hr	40,000hr
IP	IP65	IP65
Colours	Matte White	Matte White

## hugolighting.com | P: 03 942 1272 | E: info@hugolighting.com