

| Input    | Mode       | Wattage  | Rated Duration | Weight | LED Life |
|----------|------------|----------|----------------|--------|----------|
| 220-240V | Maintained | 1.2W LED | 2 Hours        | 1.2Kg  | 50,000hr |

|           |           |
|-----------|-----------|
| Frequency | Re-Charge |
| 50-60Hz   | <16hr     |

## Easy to fit Surface Mounted LED EXIT

The HUGO easy slide connect Exit Single and Double sided include all Running Man pictogram sets (EXIT sets available on Request)

Designed for speedy and efficient installation and able to be surface mounted, suspended or wall mounted (with optional side mounting bracket )

Designed to exceed brightness requirements whilst operation at very low power consumption.

As stylish and efficient fully compliant Exit luminaire

## KEY FEATURES

- Safety: Low battery voltage cut off to prevent over discharge and polarity reversal
- Construction: Fire retardant (UL94) High impact injection moulding
- Standards: AS2293:2005
- Charger: Regulated variable rate. Low battery cut-off
- Power consumption 3Watt total including standby
- Battery: High Powered Nickle Cadmium (NiCad)
- Mounting: Suspended, Surface, Wall
- Diffuser: Fire retardant Acrylic
- Dimensions: H:243, W:320, D:45mm
- Decals: Running man pictogram full set
- Charge Monitor: Green LED
- Test: Micro switch external
- Class: II
- Warranty 2yrs

