

| Input | Mode | Wattage | Rated Duration | Weight | Life |
|----------|----------------|----------------|----------------|--------|----------|
| 220-240V | Non-Maintained | 9W-D6310W-D100 | 2 Hours | 0.7Kg | 50,000hr |

| Frequency | Re-Charge | |
|-----------|-----------|--|
| 50-60Hz | <16hr | |

Surface Mounted LED Emergency 'ALL IN ONE'

Non-Maintained 10W exceptional D63-D100 classifications. Complete fitting including built in inverter, batteries and head making installation simple and easy.

Designed to exceed brightness requirements whilst operation at very low power consumption.

As stylish and efficient fully compliant emergency luminaire

Easy and quick to install

KEY FEATURES

- Safety: Low battery voltage cut off to prevent over discharge and polarity reversal
- Construction: High impact injection moulded with fire retardant material
- Standards: AS2293-2005
- Charger: Regulated variable rate. Low battery cut-off
- Power consumption:<1.5W D63 <3.0W D100
- Battery: High Powered Nickle Cadmium (NiCad) High Temp
- Mounting: Surface
- Dimensions: H:100mm Overall 125mm
- Charge Monitor: Green LED
- · Test: Micro switch external
- Class: II
- · Warranty 2yrs



SKU CODE CLASSIFICATION

EMGSM64 D63 EMGSM100 D100