

LED AC Floodlight

New technology utilising SMD2835 AC LEDs in a Matrix array to improve performance and control unwanted light spill and glare.

High IP protection at IP65 or IP66 and fitted with moisture valve to eliminate lens fogging.

Suitable for both residential and commercial applications.



Key Features

- Complete with 1.5m flex
- Suitable to operate with motion sensors
- Instant on off no cooling re strike time
- AC 2835 LEDs
- LED Life 50,000hrs
- Tempered safety glass
- Stainless Steel screws
- Excellent light and glare control
- Compact Size
- Light Weight
- IES Files (Refer Website)
- Aluminium body
- Pressure valve to control moisture inside



SKU Code	FLAC2020	FLAC2050	FLAC2100	FLAC2200
Input	230V	230V	230V	230V
Wattage	20W	50W	100W	200W
Lumen	1,800lm	4,500lm	9,000lm	18,000lm
LED Qty	24pcs	72pcs	144pcs	288pcs
Dimensions	L: 207mm H: 157mm D:30mm	L: 262mm H: 195mm D:30mm	L: 337mm H: 245mm D:31mm	L: 444mm H: 313mm D:40mm
Weight	0.75KG	1.2KG	1.8KG	4KG
Dimmable	No	No	No	No
CRI	80+	80+	80+	80+
Driver	AC	AC	AC	AC
Colour Temp	4,000K	4,000K	4,000K	4,000K
Warranty	3 years	3 years	3 years	3 years
Chip	SMD 2835	SMD 2835	SMD 2835	SMD 2835
Beam Angle	120	120	120	120
PFC	0.95	0.95	0.95	0.95
Material	Aluminium & Glass	Aluminium & Glass	Aluminium & Glass	Aluminium & Glass
IP	IP66	IP66	IP66	IP66

