

LED Highbay IP65

Introducing a Next Generation of Highbay lighting. Gone is the inefficient Mercury Vapour, Metal Halide and even HPS metal reflector highbays. Latest generation introduces massive system efficiency with up to 135+ Lumens per Watt. The HUGO LED highbay features a highly efficient driver matched to 3030 SMD LEDs. Supplied complete with flex & plug top for quick installation.



Key Features

- Rated Power [150w = 158.4w Current 0.66A Inrush Current Cold 0.83A]
- Rated Power [200w = 211.2w Current 0.88A Inrush Current Cold 1.1A]
- Complete with 1.5M flex & plug
- Working temp -30°C to +45°C Humidity 10% to 95%
- Dimming options DALI 1-10V on request
- Suitable to operate with motion sensors
- Instant on off no cooling re-strike time
- Constant current driver
- LED Life 50,000hrs (TM21 L70)
- Optical grade PC UV and fire resistant lens
- Stainless steel screws
- Excellent uniformity
- Compact size
- Light weight
- IES files (refer website)
- Aluminium body
- Mounting hook
- CRI 80+ (R9=4)
- Over current protection
- SAA Electrical approval

SKU Code	HB151-5	HB201-5
Input	230V	230V
Wattage	150W	200W
Lumen	21,000lm	27,350lm
LED Qty	182pcs	240pcs
Dimensions	D: 320mm H: 150mm	D: 320mm H: 150mm
Weight	3.2KG	3.4KG
Dimmable	Available - DALI 1-10V	Available - DALI 1-10V
CRI	80+	80+
Driver	Integral	Integral
Colour Temp	5,000K	5,000K
Warranty	5 years	5 years
Chip	SMD 3030	SMD 3030
Beam Angle	90°	90°
PFC	0.95	0.95
Material	Aluminium	Aluminium
IP	IP65	IP65